

DX22-E

GEAR-DRIVEN GRINDER



DESIGN FEATURES

HEAVY-DUTY GEARBOX

Offers superior durability

HIGH TORQUE DESIGN

Designed for heavy prep and removal

COUNTER ROTATING HEADS

Lowers operator fatigue and make the machine easy to use

COMPACT SIZE

Perfect for small areas and easy transport

LED LIGHT BAR

Improves visibility to allow the operator to monitor the floor

FOLDABLE HANDLE

Allows for easy and compact transportation

WATER TANK

4.75 gallon water tank enables wet grinding capability

MAGNETIC PLATES

Two magnetic plates 12.375" diameter allow the operator to quickly attach and detach tooling

VARIABLE SPEED CONTROL

Provides the operator with more versatility and control

SPECIFICATIONS

WORKING WIDTH	22"
MOTOR	5.5 HP SIEMENS
VOLTAGE	SINGLE PHASE 220V
WATER TANK CAPACITY	4.75 GAL
WEIGHT	465 LBS
DIMENSIONS (LXWXH)	35 X 22 X 42.5 IN
HEAD PRESSURE	310 LBS**
MAGNETIC PLATES	2 X 12.375" INCLUDED
NUMBER OF DIAMONDS	6
WORKING PLATE SPEED	0-560 RPM

PRODUCTION RATE

POLISHED CONCRETE	350 SQ. FT. PER HR.
THIN SET REMOVAL	250 SQ. FT. PER HR.
MASTIC REMOVAL	250 SQ. FT. PER HR.
+/-25 MIL COATINGS	250 SQ. FT. PER HR.
ROUGH TERRAZZO	450 SQ. FT. PER DAY

*Concrete conditions vary affecting production rates
**Weight may vary based on water tank levels and use of front weight.

COMES WITH

- Power cord holder pole
- Shroud for dust and slurry containment
- USB charging port
- 2.5 inch camlock dust port
- Water resistant Hubbell twist lock plug
- Adjustable height back wheels
- 30lb front weight



30lb front weight




75 feet of 8 gauge extension cord



6 Velcro tool holders



Robust gears to drive tool plates



Counter rotating heads make it easy for the operator to use