



SCAN FOR MORE INFO



Coverage Rate: 2,000-5,000 sq. ft/ gal
Available In: 5 Gallon Pail

DIAMAPRO SYSTEMS
MORE THAN JUST CHEMICAL



TRACTION ADDITIVE

Proprietary Blend,
Extremely Hard, Angular Aggregate

OVERVIEW

Diamapro® Traction Additive is a proprietary blend of extremely hard, angular aggregate to enhance the slip resistance of the Diamapro® UV-HS Plus System. Diamapro® Traction Additive is available in “white” and in a fine, medium or course mesh size. Diamapro® Traction Additive is non-hazardous. The shape of the aggregate provides the resin to lock on and hold it in place to increase the service life. Diamapro® Traction Additive is incorporated into the final coat of the Diamapro® UV-HS Plus System developing the highest level of additional traction with the selected mesh size.

Diamapro® Traction Additive is used in wet areas that require a minimal slip. Such as wash bays, slaughter areas, ramps, food preparation areas and more. Diamapro® Traction Additive is used only in the final coat of the Diamapro® UV-HS Plus System. Diamapro® Traction Additive is broadcasted by hand into the final coat and not mixed into the material while still in the container

GENERAL INFORMATION

- Mohs’ Hardness – 9
- Size: Fine, Medium and Course
- Must be kept dry while being stored.
- Unlimited shelf life if kept dry.

FEATURES & BENEFITS

- Extremely hard, which increases the system’s service life.
- Angular shape to provide optimum resin encapsulation.
- Heavy to enable a more even hand broadcasting.
- Extremely low moisture absorption properties increase durability.