



Diamapro Texture Additive

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

MANUFACTURER: Diamapro Systems, Inc.
ADDRESS: 4833 Sandy Porter Road
Charlotte, NC 28273

EMERGENCY PHONE:
INFORMATION PHONE:
NAME OF PREPARER:

1-800-424-9300
1-800-622-2048
Safety Director

PRODUCT NAME: Diamapro® Diamapro Texture Additive

SECTION 2 - HAZARDS IDENTIFICATION

Eye Irritation: Category 1

Aspiration Hazard: Category 1

Warning

Causes serious eye irritation. May cause respiratory irritation.



Keep container tightly closed. Wash hands thoroughly after handling. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.

Classification: Organic Powder

OSHA 29CFR 1910.1200: Combustible dust

REGULATION (EC) No 1272/2008: Not a hazardous substance or mixture

OSHA 29CFR1910.1200

WARNING – May form combustible dust concentrations in the air

REGULATION (EC) No 1272/2008: Not a hazardous substance or mixture. These products are micronized powders.

Static charges on the powders may ignite flammable atmospheres. High levels of product dust in the atmosphere may present a dust explosion hazard.



Diamacoat Texture Additive

SAFETY DATA SHEET

Other useful guides to handling organic powders include:

NFPA 77 Recommended Practice on Static Electricity

NFPA 654 Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids

NFPA 499 Recommended Practice for the Classification of Combustible Dusts and of Hazardous (Classified) Locations for Electrical Installations in Chemical Process Areas

OSHA 3371-08 Hazard Communication Guidance for Combustible Dusts

DUST HAZARD - Notification given pursuant to Table 1.5.2 of the 3rd Revision of GHS (2009).

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Chemical Name	CAS No.	Concentration (% by Weight)
Polypropylene homopolymer	9003-07-0	100

SECTION 4 - FIRST AID MEASURES

Contact with Eyes

Flush with copious amounts of water for at least 15 minutes. IMMEDIATE MEDICAL ATTENTION IS NECESSARY.

Contact with Skin

If burned by hot wax, quench immediately with cold tap water. Dry burn area and loosely cover to protect against infection. Do not apply ointment or salves. IMMEDIATE MEDICAL ATTENTION IS NECESSARY.

Inhalation

Treat as a nuisance dust. Remove victim to fresh air and provide oxygen if breathing is difficult. Immediate medical attention not normally required. No delayed effects expected.



Diamacoat Texture Additive

SAFETY DATA SHEET

Ingestion

If large quantities are ingested – IMMEDIATE MEDICAL ATTENTION IS NECESSARY. Do not give anything to an unconscious person.

Acute

None known.

Delayed and Chronic Effects

None known. Not listed by NTP, IARC, or OSHA as a carcinogen.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

OSHA FLAMMABILITY CLASS: Combustible solid

Suitable Extinguishing Media

Carbon Dioxide (CO₂), dry chemical or fine water spray. Avoid water stream on molten burning material as it may scatter and spread the fire.

Special Protective Equipment for Fire-Fighting

Wear self-contained breathing apparatus and protective clothing approved by NIOSH. Watch footing on floors and stairs because of possible melting and spreading of material. Use spray to keep containers cool.

Special Risks: Unusual Fire and Explosion Hazards

Flash point >530°F (277°C).

Melts in proximity to fires, causing slippery floors and stairs. When powder is suspended in air, these products could be FLAMMABLE/EXPLOSIVE.

In these circumstances, keep away from heat, sparks and open flames. Static charges on powders or powders in liquids may ignite flammable atmospheres. See Section 7 "HANDLING AND STORAGE" for suggestions on how to use these products under such conditions. Also refer to NFPA Bulletin 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", for safe handling procedures.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Wear rubber boots with slip-resistant soles, and NIOSH-approved dust respirator where dust occurs. See section 8.

Environmental Precautions:

Sinks in water. No known hazard to aquatic life.



Diamacoat Texture Additive

SAFETY DATA SHEET

Methods and Materials for Containment and Clean-up:

Collect with HEPA Filter Dust Collector. Ensure adequate ventilation. Do not walk through spilled material. Avoid Static charge at high levels.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe-Handling

Avoid contact with skin, eyes, and clothing. Wash hands before eating or drinking. Avoid accumulation of dust. Use only in well-ventilated areas.

Conditions for Safe Storage

Store in the original container in a cool, dry, well-ventilated area. Keep containers tightly sealed. Storage temperature: Ambient.

Storage life: N/A

Incompatible Materials

Dissolves in hydrofluoric acid.

Extra Information

- Avoid projections and probes that could lead to discharge between the charged polymer and probe.
- Never pour micronized polymers or waxes from a drum or large container directly into hot flammable solvents.
- Add micronized polymers or waxes slowly and in small quantities to hot flammable solvents.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Organic Powder	-	LTEL TWA 10-15 mg/m ³ (total dust) 3-5 mg/m ³ (respirable)	IDLH: - TWA: - TWA: -

Engineering Controls: Use adequate ventilation during heating processes or if dusty conditions prevail when handling powdered materials. For storage and ordinary handling, general ventilation is adequate.

Respiratory protection: Use a NIOSH-approved dust respirator with powdered wax. During melting or conveying in molten state, use organic vapor respirator.

Ventilation: Face velocity greater than 60 cfm (adequate to capture wax dust or fumes).



Diamacoat Texture Additive

SAFETY DATA SHEET

Eye/face protection: Chemical goggles around molten material and in dusty conditions.

Skin protection: Use heat resistant, impervious gloves to avoid repeated/prolonged skin contact with molten material and powder. Other protective garments as necessary.

Other Personal Protective Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Wash skin thoroughly with soap and warm water after handling and before smoking, eating, or applying makeup. If clothes become contaminated, change to clean clothing. Do not wear contaminated clothing until properly laundered. Further information relating to the safe handling and use of fluorocarbon polymers may be found in DWE (NIOSH), Publication No. 77-193.

Exposure Guidelines: Powdered forms may generate nuisance particulates upon handling.

ACGIH TLV = 10mg/m3. OSHA PEL 5mg/m3.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	solid, white powder
Odor	No Information Available
Odor Threshold	No Information Available
pH	8
Melting/Freezing Point	330°C
Initial Boiling Point and Boiling Range	No Information Available
Flash Point	>530°F
Evaporation Rate	No Information Available
Flammability	No Information Available
Upper/Lower Flammability or Explosive Limits	No Information Available
Auto Ignition Temperature	No Information Available
Vapor Pressure	nil
Vapor Density	No Information Available
Relative Density/Specific Gravity	0.90 g/cc
Solubility(ies)	No Information Available
Partition Coefficient: n-octanol/water	No Information Available
Decomposition Temperature	No Information Available
Viscosity	No Information Available
VOC (Volatile Organic Compounds)	0 mg/L

SECTION 10 - STABILITY AND REACTIVITY DATA

Reactivity: None under normal conditions. **Chemical Stability:** Stable under normal conditions.

Possibility of Hazardous Reactions: None under normal processing.

Condition(s) to Avoid: Extreme heat, sparks and open flame.

Substance(s) to Avoid: Pre-mixing over 24hours prior to application. Strong oxidizing agents and amines.

Hazardous Decomposition Product(s): These products may emit oxides of carbon and nitrogen



Diamacoat Texture Additive

SAFETY DATA SHEET

SECTION 11 - TOXICOLOGICAL INFORMATION

Treat as nuisance dust.

After inhalation: Inhalation of the dust may cause breathlessness, coughing, tightness of the chest and difficulty in breathing.

After eye contact: Slightly irritating to the eye. Avoid getting product airborne.

After skin contact: Slightly irritating to the skin.

After ingestion: No data.

Irritation: Causes eye irritation. May cause respiratory irritation. May cause transient irritation.

Corrosivity: No data.

Sensitization: No data.

Repeated Dose Toxicity: None known.

Mutagenicity: No data.

Toxicity for Reproduction: No data.

SECTION 12 - ECOLOGICAL INFORMATION

WASTE DISPOSAL METHOD: Assume conformity with applicable disposal regulations. Preferred method of disposal is in closed containers of enough strength to eliminate leakage at approved incineration or chemical landfill waste disposal site in accordance with local regulations. Sewage disposal is discouraged.

Toxicity: No known reports of ecotoxicity to the environment.

Persistence and Degradability: Persistent but inert in aquatic systems.

Bio accumulative Potential: The product will not bioaccumulate up the food chain.

RCRA: Is the unused product a RCRA hazardous waste if discarded? No.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposed material is not a hazardous waste. Disposal should be in accordance with local, state or national legislation. Containers must not be punctured or destroyed by burning, even when empty.



Diamacoat Texture Additive

SAFETY DATA SHEET

SECTION 14 - TRANSPORT INFORMATION

	UN NUMBER	UN PROPER SHIPPING NAME	TRANSPORT HAZARD CLASSES	PACKING GROUP	ENVIRONMENTAL HAZARDS
DOT	Not Regulated	Not Regulated	Not Regulated	Not Regulated	Not Regulated
IMO/IMDG	Not Regulated	Not Regulated	Not Regulated	Not Regulated	Not Regulated
IATA/CAO	Not Regulated	Not Regulated	Not Regulated	Not Regulated	Not Regulated

The transportation information listed above is suitable for all modes of transportation. TDG, IMO/IMDG, ICAO/IATA, 49 CFR

SECTION 15 - REGULATORY INFORMATION

United States:

TSCA (Toxic Substance Control Act): This product or its components are listed on the TSCA Inventory. This product or its components do not contain any chemicals subject to any rules or orders under TSCA sections 4, 5, 6, 7, or 8(d).

SARA 311/312 – Hazard Categories: Immediate/Acute Health (irritant): YES

SARA 302 – Extremely Hazardous Substances: Not hazardous

SARA 313 – Toxic Chemicals: Not toxic

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): Not established
CAA (Clean Air Act 1990): No data

CWA (Clean Water Act): No data

California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) - This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

Canada

WHMIS Classification: No data

Canada (DSL/NDSL): No data

Canada Ingredient Disclosure List (CIDL): No data

Chemical Safety Assessment: Glass is regarded by FDA as Generally Recognized As Safe (GRAS) for use in contact with food.



Diamacoat Texture Additive

SAFETY DATA SHEET

SECTION 16 - OTHER INFORMATION

HMIS	HMIS
Health	1
Flammability	1
Reactivity	0

Personal Protection: Safety goggles, neoprene rubber gloves, N95 respirator

Revision Date: 11/13/2025

By: Scott Thome

The information herein is based on data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results. Also this shall not establish a legally valid contractual relationship.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in use of the material.

Our products are intended for sale to industrial and commercial customers. We encourage customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications.

Warranty: The manufacturer warrants that products sold comply with specifications as represented and will perform satisfactorily if used according to the directions, or the manufacturer will refund or replace any unused portion thereof, for a period of one year from the date of manufacture. The manufacturer does not make any other warranty, or assume responsibility of any kind, expressed or implied regarding the effect or result of the products use; and assumes no responsibility of injury to vendee or third parties proximately caused by the material if reasonable safety procedures are not adhered to.