



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

MANUFACTURER: Diamapro Systems, Inc.	EMERGENCY PHONE:	1-800-424-9300
ADDRESS: 4833 Sandy Porter Road	INFORMATION PHONE:	1-800-622-2048
Charlotte, NC 28273	NAME OF PREPARER:	Safety Director

PRODUCT NAME: Diamapro® Diamapro-ESD Spartic Part B

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview: Danger. May cause allergic skin reaction. May cause skin, eye, and respiratory tract irritation. Harmful by inhalation and if swallowed.

Component Information/Information on Non-Hazardous Components: None known.

GHS Classification of the Substance or Mixture

PHYSICAL HAZARDS:

None known.

HEALTH HAZARDS:

Inhalation -- Acute toxicity: Category 4

Respiratory Sensitization: Category 1

Skin Sensitization: Category 1

Specific Target Organ Toxicity – Single Exposure Respiratory: Category 3

Specific Target Organ Toxicity – Repeated Exposure Inhalation (Lungs): Category 2

DANGER

Hazard Statement(s):

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs (Lungs) through prolonged or repeated exposure.

Diamapro-ESD Spartic Part B

SAFETY DATA SHEET



Precautionary Statement(s):

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P171: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: In case of inadequate ventilation, wear respiratory protection that meets the requirements in OSHA's Respiratory Protection Standard (29 CFR 1910.134) or regional standards.

Response:

P370 + P378: In case of fire, use water spray, carbon dioxide, dry chemical, or foam for extinction.

P303+P361+P353: IF ON SKIN (or hair), Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340: IF INHALED, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P311: IF SWALLOWED, immediately call a POISON CENTER or doctor/physician.

P305+P351+P338: IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs, get medical advice/attention.

P337+P313: If eye irritation persists, get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P235: Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None known.

Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

Other Information:

Inhalation: Isocyanate vapors or mist at concentrations above the exposure limits or guidelines can cause a burning sensation and irritate the mucous membranes in the nose, throat, and lungs, resulting in symptoms of running nose, sore throat, coughing, chest discomfort, shortness of breath and difficulty in breathing. Persons with specific pre-existing as well as non-specific bronchial hyperreactivity can respond to concentrations of isocyanate below the exposure limit or guidelines with asthma or asthma-like symptoms. Exposure above these limits or guidelines may lead to bronchitis, bronchial spasm, and fluid in lungs (pulmonary edema). Some persons may see a delay of these symptoms up to several hours after exposure, and these effects are usually reversible.

Skin: May cause skin irritation with symptoms of reddening, itching, and swelling. Can cause sensitization with symptoms of reddening, itching, swelling and rash. Cured material is difficult to remove from the skin.

Eye: May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling, particularly with product vapor, mists, or aerosol. May cause temporary corneal injury.

Ingestion: May cause irritation of the digestive tract with symptoms that include abdominal pain, nausea, vomiting, and diarrhea.

Carcinogenicity: No carcinogenic substances as defined by IARC, NTP and/or OSHA.

See Section 12 for Ecological Information.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

The specific chemical identity and exact concentration of composition has been withheld as a trade secret.

Chemical Name	CAS No.	Concentration (% by Weight)	Comments
Homopolymer of Hexamethylene Diisocyanate	28182-81-2	80-100CA	Acute toxicity Category 4 Inhalation. Respiratory sensitization Category 1 Specific target organ toxicity – single exposure Category 3 Respiratory system. Specific target organ toxicity – repeated exposure Category 2 Inhalation Lungs.
Hexamethylene 1,6-Diisocyanate	822-06-0	<0.3CA	Acute toxicity Category 4 Oral. Acute toxicity Category 1 Inhalation. Skin corrosion Category 1 Serious eye damage Category 1 Respiratory sensitization Category 1. Skin Sensitization Category 1. Specific target organ toxicity – single exposure Category 3 Respiratory System.

See Section 11 for Toxicological Information.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 4 - FIRST AID MEASURES

Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Skin: In case of skin contact, wash affected areas with soap and water. Immediately remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Thoroughly clean shoes before reuse. Wash clothing and other apparel before reuse.

Eye: In case of contact, flush eyes with plenty of lukewarm water. Use fingers to ensure that eyelids are separated and that the eye is being irrigated. Get medical attention.

Ingestion: If ingested, do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Suitable Extinguishing Media: Dry chemical, carbon dioxide, foam. Use water spray to keep fire-exposed containers cool.

Unsuitable Extinguishing Media: High volume water jet.

Unusual Fire and Explosion Hazards

Firefighters should wear NFPA approved self-contained breathing apparatus and full protective clothing. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. Toxic and irritating gases/fumes, including heated diisocyanate that is considered extremely dangerous, may be given off during burning or thermal decomposition.

Hazardous Combustion Products

carbon dioxide, carbon monoxide, oxides of nitrogen, hydrogen cyanide, isocyanate, and isocyanic acid. dense black smoke, and other compounds unidentified

Advice for Fire Fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots, and gloves. Vapors or mist may be a fire and explosion hazard when exposed to high temperature or ignition. Closed container may forcibly rupture under extreme heat. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture. Toxic gases/fumes may be given off during burning or thermal decomposition.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Wear appropriate personal protective equipment. Evacuate surrounding areas and isolate the area. Keep unnecessary and unprotected personnel from entering. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Implement site emergency response plan.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform authorities if the product has caused environmental pollution (sewers, drains, waterways or soil).

Methods and Materials for Containment and Clean-up

Cleanup personnel must use appropriate personal protective equipment. Evacuate and keep unnecessary personnel out of spill area. Remove all sources of ignition, including flames, heat, and sparks. Stop leak if without risk. Move containers from spill area. Dike or dam spilled material with non-combustible, absorbent material (e.g., sand, earth, vermiculite, or diatomaceous earth) and control further spillage, where possible. Make certain the absorbent material soaks up all liquids.

Collect and place spilled material in container (e.g., 55-gal salvage drum) for proper disposal according to appropriate local, state, and federal regulations. Repeat application of absorbent material until all liquid has been removed from the surface. Do not fill the salvage container more than two-thirds full to allow for any expansion, and do not tighten the lid on the container. Store salvage container (make certain lid is loose to allow release of carbon dioxide) in a well-ventilated, isolated, and cool area for at least 72 hours. Properly dispose of the waste material and any contaminated equipment in accordance with existing federal, state, and local regulations.

Decontaminate the spill surface area with a neutralization solution. A neutralization solution can be prepared with a combination of two solutions mixed 1:1 by volume: (Solution 1): Mineral Spirits (80%), VVM&P Naptha (15%) and Household Detergent (5%); (Solution 2): Monoethanolamine (50%) and water (50%). Other neutralization solutions include ZEP® Commercial Heavy-Duty Floor Stripper, EASY OFF® Grill and Oven Cleaner, a solution of Simple Green® Pro HD Heavy-Duty Cleaner (50%) and Household Ammonia (50%), and a solution of Fantastic® Heavy Duty All Purpose Cleaner (90%) and Household Ammonia (10%). Check for residual contamination using Swype® test kits from Colorimetric Laboratories, Inc. (Telephone 847-803-3737) and follow directions provided by the test kits. Repeat decontamination as necessary.

Do not allow spilled material or wash water to enter sewers, surface waters or groundwater systems.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 7 - HANDLING AND STORAGE

Handling: Do not breathe vapors or spray mist. Avoid contact with eyes or skin. Avoid contact with clothing. Use only with adequate ventilation and personal protection. Remove contaminated personal protective equipment (PPE), then wash hands and face thoroughly after handling and before eating and drinking. Keep container closed when not in use. Empty containers retain product residue and can be hazardous. Do not get in eyes, on skin or on clothing. Do not ingest. Avoid release to the environment. Either single inhalation exposure to a relatively high concentration or repeated inhalation exposures to a relatively lower contamination can produce asthmatic sensitization. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination with moisture is suspected.

Storage: Storage period is 6 months after delivery. Maximum storage temperature is 50°C (122°F). Keep away from food products during use and storage. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled, unapproved, or reactive containers. Use appropriate containment to avoid environmental contamination. Personnel education and training in the safe use and handling of this product are required under OSHA Hazard Communication Standard 29 CFR 1910.1200.

Incompatible Materials or Ignition Sources: Hazardous polymerization does not occur. Avoid water, amines, strong bases, alcohols, and copper alloys.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Special Note for Exposure Control: Consult local authorities for further acceptable exposure limits.

Exposure Limits/ Guidelines

Chemical Name	Result	ACGIH/OSHA
Homopolymer of Hexamethylene	STEL	0.001 pm
Diisocyanate (CAS 28182-81-2)	TWA	0.005 ppm
	PEL	No data available.
Hexamethylene-1,6- Diisocyanate	STEL	No data available.
(CAS 822-06-9)	TWA	0.005 ppm
	PEL	No data available.

Engineering Measures/Controls

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts, and thermal decomposition products below appropriate airborne concentration standards and guidelines.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent the build-up of explosive atmospheres and to prevent off-gases from entering the workplace.

Environmental Exposure Controls

Avoid release to the environment. Construct a dike to prevent spreading of spills. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Hygiene Measures

Wash hands, forearms, and face thoroughly after handling chemical products, before eating and drinking, smoking, or using the lavatory and at the end of the working period.

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Respiratory: In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use positive pressure supplied air respirator when airborne concentrations are not known, when airborne levels are 10 times the appropriate TLV, and when spraying is performed, or product is applied by aerosol in a confined space or area with limited ventilation. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Contact health and safety professional or manufacturer for specific information. A respirator that is recommended or approved for use in isocyanate-containing environments, including air-purifying or fresh air-supplied, may be necessary for spray applications or other situations such as high temperature use that may produce unacceptable inhalation exposures.

A supplied air respirator (either positive pressure or continuous flow-type) is recommended. Before an air-purifying respirator can be used, air monitoring must be performed to measure airborne concentrations of HDI monomer and HDI polyisocyanate. Specific conditions under which air-purifying respirators can be used are provided herein. Observe OSHA regulations for respirator use (29 CFR 1910.134).



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

When coatings containing isocyanate are spray applied, good industrial safety practice requires the use of some form of respiratory protection. During spray application of coatings containing this product, the use of a supplied-air (either positive pressure or continuous flow-type) respiratory is mandatory when one or more of the following conditions exist:

1. The airborne isocyanate concentrations are not known.
2. The airborne isocyanate monomer concentrations exceed 0.05 ppm averaged over eight (8) hours. This is 10 times the 8- hour TWA or the 15-minute STEL exposure limits.
3. The airborne polyisocyanate (polymeric, oligomeric) concentrations exceed 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes. This is 10 times the 8-hour TWA or the 15-minute STE'L exposure limits.
4. Operations are performed in a confined space (See OSHA Confined Space Standard, 29 CFR 1910.146).

A properly fitted air-purifying (combination organic vapor and particulate) respirator, proven by test to be effective in isocyanate-containing spray paint environments, and used in accordance with all recommendations made by the manufacturer, can be used when all following conditions are met:

1. The airborne isocyanate monomer concentrations are not known.
2. The airborne isocyanate monomer concentrations exceed 0.05 ppm averaged over eight (8) hours. This is 10 times the 8-hour TWA or the 15-minute STEL exposure limits.
3. The airborne polyisocyanate (polymeric, oligomeric) concentrations exceed 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes. This is 10 times the 8-hour TWA or the 15-minute STE'L exposure limits.
4. A NIOSH-certified End-Of-Service-Life Indicator or a change schedule based upon objective information or data is used to ensure that cartridges are replaced before the end of their service life. In addition, pre-filters should be changed whenever breathing resistance increases due to particulate buildup.

Eye/Face: Use chemical resistant goggles. Chemical safety goggles in combination with a full face shield must be used if a splash hazard exists.

Hands: Use permeation resistant gloves such as butyl rubber, nitrile rubber, or neoprene.

Skin/Body: Wear rubber or plastic apron and permeation resistant clothing, chemical-resistant gloves, and longsleeved shirts, and pants. Remove and wash contaminated clothing before re-use.

Special Requirements: All applicants who are assigned to an isocyanate work area should undergo a pre-placement medical evaluation. A history of eczema or respiratory allergies such as hay fever, are possible reasons for medical exclusion from isocyanate work areas. Applicants with a history of prior isocyanate sensitization should be excluded from further work with isocyanates. A comprehensive annual medical surveillance program should be instituted for all employees who are potentially exposed to diisocyanates. Once a worker has been diagnosed as sensitized to any isocyanate, no further exposure should be permitted.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

General Industrial Hygiene Considerations

Keep away from food and drink. Wash hands and face after use. Educate and train workers in the safe use and handling of this product. Emergency showers and eye wash stations should be available. Follow all label instructions.

Key to Abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

MSHA = Mine Safety and Health Administration

TWA = Time-Weighted Averages are based on 8h/day 40hr/week exposures

STEL = Short Term Exposure Limits are based on 15-minute exposures

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid, colorless to pale yellow.
Odor	Minimal to no odor.
Odor Threshold	No data available.
pH	No data available.
Melting Point	No data available.
Freezing Point	No data available.
Initial Boiling Point and Boiling Range	Decomposes.
Flash Point	170°C (338°F) ca
Evaporation Rate	No data available.
Flammability	No data available.
Upper/Lower Flammability or Explosive Limits	No data available.
Auto-ignition Temperature	No data available.
Vapor Pressure	No data available.
Vapor Density	No data available.
Relative Density	No data available.
Specific Gravity	1.12 ± 0.1
Water Solubility(ies)	Reacts.
Partition Coefficient: n-octanol/water	No data available.
Auto-ignition Temperature	No data available.
Decomposition Temperature	No data available.
Viscosity	No data available.
VOC (Volatile Organic Compounds)	<100 g/L

Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 10 - STABILITY AND REACTIVITY DATA

Chemical Stability: Stable under normal conditions of use and storage.

Possibility of Hazardous Reactions: Contact with moisture, other materials that react with isocyanates, or temperatures above 177°C (350°F) may cause polymerization.

Conditions to Avoid: Heat, flames, and sparks.

Incompatible Materials: Water, amines, strong bases, alcohols, copper alloys.

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen, dense black smoke, hydrogen cyanide, isocyanate, isocyanic acid, and other compounds unidentified.

SECTION 11 - TOXICOLOGICAL INFORMATION

Data on the product is not available. Data on a similar product is provided.

ACUTE TOXICITY

Hexamethylene-1,6-diisocyanate Homopolymer (CAS 28182-81-2)

LD50 Oral Rat, Female $\geq 2,500$ mg/kg

LD50 Inhalation Rat, Female 0.390 – 0.543 mg/l 4h

LD50 Dermal Rabbit $> 2,000$ mg/kg

LD50 Dermal Rat $> 2,000$ mg/kg

Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

LD50 Oral Rat, Female 746 mg/kg

LD50 Inhalation Rat, Female 0.124 mg/l 4h

LD50 Dermal Rat $> 7,000$ mg/kg

IMMEDIATE (ACUTE) EFFECTS

Hexamethylene-1,6-diisocyanate Homopolymer (CAS 28182-81-2)

Skin Corrosion/Irritation (Rabbit, 4h): Slight skin irritation. Skin sensitizer.

Eye Irritation (Rabbit): Slight irritant.

Inhalation (Mouse): Respiratory sensitizer.

STDT (One-time exposure): May cause respiratory irritation.

Carcinogenicity: No data available.



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

Skin Irritation (Rabbit): Corrosive.
Eye Irritation (Rabbit): Corrosive.
Dermal (Human): Sensitizer.
Respiratory (Guinea Pig): Sensitizer.

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity: Hexamethylene-1,6-diisocyanate Homopolymer (CAS 28182-81-2)

Acute and Prolonged Toxicity to Fish: LC50 100 mg/l (Zebra Fish, 96h), Acute Toxicity to Aquatic Invertebrates: EC50 100 mg/l (water flea, 48 h).

Persistence and Degradability: Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

Not readily degradable.

Bio-accumulative Potential: Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

Accumulation is not expected.

Other Adverse Effects: Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

An accumulation in aquatic organisms is not expected.

Other Information: Hexamethylene-1,6-diisocyanate (CAS 822-06-0)

LC0: ≥ 82.8 mg/l (Zebra Fish, 48 h)

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Dispose in accordance with Federal, State, and Local laws and regulations. The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Precautions

Do not heat or cut container with electric or gas torch. Recondition or dispose of empty container in accordance with governmental laws and regulations. Do not reuse empty container without proper cleaning. Label precautions also apply to this container when empty.

Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

SECTION 14 - TRANSPORT INFORMATION

	UN Number	UN Proper Shipping Name	Transport Hazard Class(es)	Packing Group	Environmental Hazards
DOT	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
IMO/IMDG	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
IATA/CAO	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special Precautions for User: When in individual containers containing less than the Product RQ, this product ships as non-regulated.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15 - REGULATORY INFORMATION

State Right to Know

Component	CAS	MA	NJ	PA
Hexamethylene-1,6-diisocyanate Homopolymer	28182-81-2	28182-81-2	28182-81-2	28182-81-2
Hexamethylene-1,6-diisocyanate	822-06-0 -	-	822-06-0	-

Inventory

Component	CAS	Canada DSL	Canada NDSL	TSCA
Hexamethylene-1,6-diisocyanate Homopolymer	28182-81-2	Listed	-	Listed
Hexamethylene-1,6-diisocyanate	822-06-0	Listed	-	Listed

United States

Environment

U.S. – CERCLA/SARA – Hazardous Substances and their Reportable Quantities: **None**

U.S. – SARA – Section 311/312 Hazard Categories: **Acute Health Hazard, Chronic Health Hazard**

U.S. – CERCLA/SARA – Section 302 Extremely Hazardous Substances TPQs: **None**

U.S. – CERCLA/SARA – Section 313 – Emissions Reporting: **None**

U.S. – CERCLA/SARA – Section 313 – PBT Chemical Listing: **None**



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components: **None**

U.S. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 372.65) Supplier Notification Required Components: **None**

U.S. Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261): **Under RCRA it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.**

United States – California

Environment

- U.S. – California – Proposition 65 – Carcinogens List: **None**
- U.S. – California – Proposition 65 – Developmental Toxicity: **None**
- U.S. – California – Proposition 65 – Maximum Allowable Dose Levels (MADL): **None**
- U.S. – California – Proposition 65 – No Significant Risk Levels (NSRL): **None**
- U.S. – California – Proposition 65 – Reproductive Toxicity – Female: **None**
- U.S. – California – Proposition 65 – Reproductive Toxicity – Male: **None**

Based on information provided by Diamapro Systems® suppliers, this product is considered “DRC Conflict Free” as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716, File No. S7-40-10, Date 08-22-212).

SECTION 16 - OTHER INFORMATION

Personal Protection: protective clothing, impervious gloves, safety goggles, OSHA/NIOSH-approved respirator

Revision Date: 11/13/2025

By: Scott Thome

The information herein is based on data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results. Also this shall not establish a legally valid contractual relationship.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use



Diamapro-ESD Spartic Part B

SAFETY DATA SHEET

of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in use of the material.

Our products are intended for sale to industrial and commercial customers. We encourage customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications.

Warranty: The manufacturer warrants that products sold comply with specifications as represented and will perform satisfactorily if used according to the directions, or the manufacturer will refund or replace any unused portion thereof, for a period of one year from the date of manufacture. The manufacturer does not make any other warranty, or assume responsibility of any kind, expressed or implied regarding the effect or result of the products use; and assumes no responsibility of injury to vendee or third parties proximately caused by the material if reasonable safety procedures are not adhered to.