

DIAMAPRO® SYSTEMS DCP-PRO



SPECIFICATIONS:

Weight	295 LBS
Dimensions (L x H x W)	50" X 42" X 23"
Motor (Torque)	15.6 Nm (140in-lb)
Pumps	Internal Gear Pump
Tanks	2 X 10 Gallon
Power	110V (Wall Power)
Battery	24V Battery
Control	Adjustable Wand with Variable Speed
Ratio	1:1
Flow Rate	0-0.3 GPM
Wash Out Tank	3 Gallons



PAIRS WELL WITH
DIAMAPRO SYSTEMS®
DIAMAPRO-JOINT 2.0 FILL

The DCP-Pro's efficient battery management and ergonomic design ensures maximum comfort, and uninterrupted performance throughout the workday.

Diamapro Systems' DCP-Pro dual component pump is equipped with two power options. The pump can be easily plugged into any 110V outlet or it can be switched to its battery powered option. The DCP-Pro features an approximate eight hour total 24V battery system and a built-in battery life indicator. This pump ensures all-day productivity without interruptions.

- Dual ten-gallon tanks, offer extended operational time before requiring a refill. Clean-up is made effortless with the DCP-Pro's built in integrated washout system with a three gallon cleaning fluid tank.
- The DCP-Pro is designed for operator comfort by enabling a stand-up application, sparing users from having to kneel.
- It includes an application wand with an adjustable flow grip handle, elbow brace, and customizable height adjustments to suit various operators.
- The DCP-Pro's robust frame, casters, handles and components are built to stand up to the harshest job sites.

Perfect for use on:

- Large joint filling floor projects
- Polyurea joint filler projects
- Epoxy joint filler projects
- Application of some polyaspartic coatings



DIAMAPRO® SYSTEMS DCP-PRO



CONTROLLED MATERIAL
FLOW GRIP



ERGONOMICALLY DESIGNED
APPLICATION WAND



BATTERY LIFE INDICATOR AND
EASY FLIP ELECTRICAL SYSTEM



DUAL ON-BOARD 24V BATTERIES



3 GALLON INTEGRATED
WASHOUT SYSTEM



2 BALL VALVES TO
FLUSH PUMP LINES



LARGE TANK LIDS
FOR EASY ACCESS



QUICK JOINT FILLING
VS. CARTRIDGE APPLICATION



USE BATTERY POWER OR WALL
OUTLET POWER

Why choose the DiamoPro Systems' DCP-Pro Dual Component Pump

- Reduce labor costs by significantly increasing application speed on concrete floor projects
- Reduce material waste with a controlled material flow grip
- Easiest pump on the market to clean
- Integrated three gallon tank washout system. Just flip 2 ball valves to flush the pump lines
- Easy flip electrical system 110V or Battery with 8 hour battery life indicator
- Ergonomically designed application wand has an adjustable flow grip handle, elbow brace, and customizable height adjustments to suit various operators
- Production rate to 5,000 lineal joint filling feet per day
- Quick joint filling vs. cartridge application
- Twin tanks each hold 10 gallons of product
- Large tank lids allow easy access
- Dispenses in a 1:1 ratio
- Built Jobsite Tough with a heavy duty frame and casters
- Easy grip handles for job site maneuverability
- Included tank shut off valve



**NIAGARA
MACHINE, INC.**

ESTABLISHED 1954

www.niagaramachine.com

800-622-2048

7 SHOWROOM / WAREHOUSE LOCATIONS, 8 REPAIR CENTERS, 9 SALES LOCATIONS

**HEADQUARTERS
CHARLOTTE
NORTH CAROLINA**
4833 Sandy Porter Rd.
Charlotte, NC 28273
(704) 329-5701

**ERIE
PENNSYLVANIA**
325 West Front
Erie, PA 16507
(814) 455-8838

**DEBARY
FLORIDA**
889 S. Charles Richard Beall Blvd.
Debary, FL 32713
(386) 320-0406

**GLOUCESTER CITY
NEW JERSEY**
500 South Broadway
Gloucester City, NJ 08030
(856) 742-7200

**CARLSTADT
NEW JERSEY**
435 Oehler Place
Carlstadt, NJ 07072
(201) 758-5422

**GRAND PRAIRIE
TEXAS**
2122 113th St.
Grand Prairie, TX 75050
(682) 320-8153

**DENVER
COLORADO**
2590 W. 2nd Ave.
Denver, CO 80219
(720) 354-9200