	= SECTION 1 - IDENTIFICA	411UN ======		
MANUFACTURER: ADDRESS : PRODUCT NAME: DiamaPro PRODUCT CODE: DPDG&S		INI	IERGENCY PHONE: FORMATION PHONE: ME OF PREPARER:	1-800-622-2048
=======================================	SECTION 2 - HAZARDS II	DENTIFICATION		
HAZARD RISK CLASSIFICATION				
SIGNAL WORD:				
PICTOGRAM:				
HAZARD CLASS	HAZAF	RD CATEGORY		
HAZARD STATEMENTS: H303 May be harmfu	l if swallowed			
PRECAUTIONARY STATEMENTS:	:			
PREVENTION:				
RESPONSE:				
STORAGE:				
DISPOSAL:				
=======================================	SECTION 3 - COMPOSITION	ON/INFORMATIO	ON ON INGREDIENTS =	
COMPONENT	CAS NUMBER	PERCENT	OSHA PEL ACGIH T	LV OTHER
Di propylene Glycol N-Butyl Ethe	er 29911-28-2	1-10	NOT ESTABLISHED	
PRIMARY ROUTES OF EXPOSUR	E: Skin co	Skin contact		
SKIN: Prolonged or re INHALATION: Inhalat	with eyes may cause irritation epeated contact may cause irri ion of vapor or mist can cause nticipated route of exposure.	itation. e irritation of nose,	_	
CHRONIC HEALTH EFFECTS: No anticipated chron No known effects on	ic effects. MEDICAL CONDITIO other illnesses.	INS GENERALLY AG	GRAVATED BY EXPOSURE:	
	SECTION 4 - FIRST AID M	IEASURES ====		
EYES: Flush with large amounts of	of water for 15 minutes, lifting	g upper and lower o	eyelids. If irritation persists	, seek medical attention.
SKIN CONTACT: Wash contamin	ated area with soap and wate	r. Remove and laur	nder contaminated clothing	,

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

INGESTION: If a large amount is ingested, give water or milk, and induce vomiting. Seek medical attention.

FLASH POINT: Greater than 200 F METHOD USED: SETAFLASH
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical, or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

============== SECTION 6 - ACCIDENTAL RELEASE MEASURES ==========================

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

============= SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION ======================

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or ares with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

====== SECTION 9 - PHY	SICAL AND CHEMICAL PROPERTIES =================			
PHYSICAL STATE: Liquid	COLOR: Various colors			
ODOR: Amine or ammonia odor	SOLUBILITY IN WATER: Dilutable			
SPECIFIC GRAVITY (H2O=1): 1.03	VAPOR DENSITY: Heavier than air.			
BOILING RANGE:	EVAPORATION RATE: Slower than nBuAc			
COATING V.O.C.: 148 g/l (1.24 lb/gl)				
======================================				
STABILITY: Stable under normal conditions and handling.				
CONDITIONS TO AVOID: None known				
INCOMPATIBILITY (MATERIALS TO AVOID): None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.				
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.				
HAZARDOUS POLYMERIZATION: Will not occur.				
======================================				
SENSITIZATION:				
None known. CARCINOGENICITY:				
There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard. REPRODUCTIVE TOXICITY:				
There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity. TERATOGENICITY (BIRTH DEFECTS):				
There is no data available to indicate any components present at greater than 0.1% may cause birth defects. MUTAGENICITY:				
There is no data to indicate that any component present at greater than 0.1% will alter DNA.				
======= SECTION 12 - EC	OLOGICAL INFORMATION ====================================			
ENVIRONMENTAL DATA:				
Contains ammonia or amines which may be toxic to aquatic life.				
======= SECTION 13 - DIS	POSAL CONSIDERATIONS ====================================			
This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261; however, state, and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.				
======================================				
SHIPPING NAME:				

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS

CAS NUMBER

STATE CODE

STATE CODE

HMIS CODES: H F R P

Prepared By: S. Thome Revision Date: 12/10/2022

2

The information herein is based on data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results. Also this shall not establish a legally valid contractual relationship.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in use of the material.

Our products are intended for sale to industrial and commercial customers. We encourage customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications.

Warranty: The manufacturer warrants that products sold comply with specifications as represented and will perform satisfactorily if used according to the directions, or the manufacturer will refund or replace any unused portion thereof, for a period of one year from the date of manufacture. The manufacturer does not make any other warranty, or assume responsibility of any kind, expressed or implied regarding the effect or result of the products use; and assumes no responsibility of injury to vendee or third parties proximately caused by the material if reasonable safety procedures are not adhered to.