Date Revised: 11/01/2017

MANUFACTURER: DiamaPro Systems, Inc. EMERGENCY PHONE: 1-800-424-9300
ADDRESS: 325 W. Front Street INFORMATION PHONE: 1-800-622-2048
Erie. PA 16507 NAME OF PREPARER: Safety Director

PRODUCT NAME: DiamaPro Line Striping, SAFETY BLUE

PRODUCT CODE: DPLS-Blue

========= SECTION 2 - HAZARDS IDENTIFICATION ===================================

HAZARD RISK CLASSIFICATION

SIGNAL WORD: DANGER

PICTOGRAM:

GHS07 – EXCLAMATION MARK GHS08 – HEALTH HAZARD

HAZARD CLASS HAZARD CATEGORY

ACUTE TOXICITY CATEGORY 4 INHALATION

SKIN CORROSION / IRRITATION CATEGORY 2

SERIOUS EYE DAMAGE / EYE IRRITATION CATEGORY 2 AND 2A
CARCINOGENICITY CATEGORY 1 (BOTH 1A AND 1B)

TOXIC TO SPECIFIC TARGET ORGAN CATEGORY 1

TOXICITY - SINGLE EXPOSURE

HAZARD STATEMENTS:

H303 May be harmful if swallowed
H315 Causes skin irritation
H319 Causes serious eye irritation

H332 Harmful if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation
H350-1 May cause cancer by inhalation

Chemical(s) which may be considered a cancer hazard by IARC and / or NTP. Refer to Section 11 for further information.

PRECAUTIONARY STATEMENTS:

PREVENTION:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breath dust/fume/gas/mist/vapors or spray.

P264 Wash hands and any exposed area thoroughly after handling.

P270 Do not eat, drink or smoke while using this product.

P271 Use only outdoors or in well-ventilated area.

P280 Wear protective impervious gloves/OSHA approved eye protection/face protection.

RESPONSE:

P301+P312 If swallowed: Immediately call a Poison Center / doctor if you feel unwell.

P302 + P352 If on skin: Wash with plenty of water

P304 + P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

P308 + P313 If exposed or concerned: Get medical advise / attention.

P321 Specific treatment (see on this label)

P330 Rinse mouth.

P332 + P313 If skin irritation occurs: Get medical advise / attention.
P337 + P313 If eye irritation persists: Get medical advise / attention.

P363 Wash contaminated clothing before reuse.

STORAGE:

P402 Store in dry place.

P403 + P233 Store in well-ventilated place. Keep container tightly closed.

P405 Store locked up.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national

/international regulations.

Date Revised: 11/01/2017

======= SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ======================

	WEIGHT	EXPOSUR	E LIMITS	
COMPONENT	CAS NUMBER	PERCENT	OSHA PEL ACGII	H TLV OTHER
#* Microcrystalline Silica (Quartz)	13463-67-7	1 - 10		
			10 mg/m3	10 mg/m3
Titanium Dioxide	2786-76-7	1-10	-	-
			10 mg/m3	10 mg/m3

^{*}Chemical(s) that are chronic health hazards. Refer to Section 3 for further information.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. Inhalation: Inhalation of vapor or mist can cause irritation of nose, throat and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to relatively low portion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. If symptoms persist, seek medical attention.

INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

======== SECTION 5 - FIRE AND EXPLOSION HAZARD DATA =============================

FLASH POINT: No Flash METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

====== SECTION 6 - ACCIDENTAL RELEASE MEASURES =================================

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Date Revised: 11/01/2017

Keep containers from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see Section 10). Keep containers tightly closed. It is advised that material be used within one year of manufacture, rotate stock.

OTHER PRECAUTIONS:

All empty containers under normal use conditions. Should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

RESPIRATORY PROTECTION:

No special requirements under normal conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing gloves impervious to solvents and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

======= SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ===========================

PHYSICAL STATE: Liquid
ODOR: Amine or ammonia odor
SPECIFIC GRAVITY (H2O=1): 1.1

BOILING RANGE: COATING V.O.C.: 56 q/l (0.46 lb/ql) COLOR: Various colors
SOLUBILITY IN WATER: Dilutable
VAPOR DENSITY: Heavier than air.

EVAPORATION RATE: Slower than nBuAc

STABILITY:

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

======== SECTION 11 - TOXICOLOGICAL INFORMATION ================================

SENSITIZATION:

None known.

CARCINOGENICITY:

The indicated chemical(s) is listed by ICGIH, NTP, or OSHA as a known human carcinogen (See Section 2). IARC has classified respirable crystalline silica in the form of quartz or cristobalite as a group 1 carcinogen. NTP classifies respirable crystalline silica as "reasonably anticipated to be a carcinogen". Because this product is a free flowing liquid, dust inhalation is not an expected route of exposure.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

Date Revised: 11/01	/2017			
=======================================		SECTION 12	- ECOLO	GICAL INFORMATION ============
ENVIRONMENTAL D No known effects or c		ırds. No data a	vailable.	
===========		SECTION 13	- DISPOS	AL CONSIDERATIONS
however, state and lo	cal regulat ar superna	ions maybe motant and flush	ore restric	vaste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, tive. Coagulate the emulsion by the stepwise addition of ferric chloride and ical sewer. Incinerate liquid and contaminated solids in accordance with
===========		SECTION 14	TRANSF	PORT INFORMATION ==========
SHIPPING NAME: Not regulated.				
=========		SECTION 15 -	REGULA	TORY INFORMATION ==========
All ingredients of this substance inventory.	product are	e listed, or are	excluded	from listing, on the US Toxic Substances Control Act (TSCA) chemical
This product does not 372) above de minimi		•	ect to the r	reporting requirements of SARA Title III, Section 313 (40CFR
the requirements of C	ntain a che alifornia P Crystalline	mical known to roposition 65. Silica, which	when in th	e of California to cause cancer, birth defects or reproductive harm, subject to the respirable form is a chemical know to the state of California to cause sition 65.
STATE LISTED COM	PONENTS	CAS NU	MBER	STATE CODE .
	======	SECTION 16 -	OTHER I	NFORMATION ==========
REVISION DATE: 02/ HMIS CODES: H	F	R 0	P E	
_	·	-	_	