SAFETY DATA SHEET

Date Revised: 11	/01/2017						
	======== SECTION 1 - IDEI	NTIFICATION ====================================					
MANUFACTURER	: DiamaPro Systems						
ADDRESS :	325 W. Front Stree	et INFORMATION PHONE: 1-800-622-2048					
Erie, PA 16507		NAME OF PREPARER: Safety Director					
PRODUCT NAME	DiamaPro Line Striping, SA	,					
PRODUCT CODE: DPLS-Green							
	======= SECTION 2 - HAZA	ARDS IDENTIFICATION ====================================					
HAZARD RISK CL							
SIGNAL WORD: [DANGER						
PICTOGRAM:							
GHS07 - EXCLAN	IATION MARK	GHS08 – HEALTH HAZARD					
HAZARD CLASS		HAZARD CATEGORY					
ACUTE TOXICITY							
SKIN CORROSIO							
	MAGE / EYE IRRITATION	CATEGORY 2 AND 2A					
CARCINOGENICI		CATEGORY 1 (BOTH 1A AND 1B)					
	FIC TARGET ORGAN	CATEGORY 1					
TOXICITY - SINGI	E EXPOSURE						
		avallowed					
H303	May be harmful if						
H315	Causes skin irrita						
H319	Causes serious e	•					
H332	Harmful if inhaled						
H334		y or asthma symptoms or breathing difficulties if inhaled					
H334	May cause respire						
H350-1	May cause cance	r by inhalation					
	(07 A TEMENTO						
PRECAUTIONAR	T STATEMENTS:						
PREVENTION:							
	special instructions before us						
		tions have been read and understood.					
	oreath dust/fume/gas/mist/va						
	ands and any exposed area t						
	eat, drink or smoke while usi						
	y outdoors or in well-ventilat						
P280 Wear pr	otective impervious gloves/0	DSHA approved eye protection/face protection.					
RESPONSE:							
P301+P312		nediately call a Poison Center / doctor if you feel unwell.					
P302 + P352 If on skin: Wash v		with plenty of water					
P304 + P340	If inhaled: Remov	e person to fresh air and keep comfortable for breathing.					
P305 + P351 + P3	38 If in eyes: Rinse o	cautiously with water for several minutes. Remove contact lenses, if present					
and easy to do. C							
P308 + P313	If exposed or con	cerned: Get medical advise / attention.					
P321		it (see on this label)					
P330	Rinse mouth.						
P332 + P313	If skin irritation of	ccurs: Get medical advise / attention.					
P337 + P313	If eye irritation pe	ersists: Get medical advise / attention.					
P363		ed clothing before reuse.					
		-					
STORAGE:							
P402	Store in dry place.						
		ce. Keep container tightly closed.					
P405	Store locked up.						
DISPOSAL:							
P501	Store separately. Dispose of	of contents/ container in accordance with local/ regional/national					
/international reg							

/international regulations.

SAFETY DATA SHEET

Date Revised: 11/01/2017

COMPONENT	WEIGHT CAS NUMBER	EXPOSUR PERCENT	E LIMITS OSHA PEL ACGI	IH TLV OTHER
#* Microcrystalline Silica (Quartz)	13463-67-7	1 - 10	10 ma/m3	10 ma/m3
Titanium Dioxide	2786-76-7	1-10	To mg/mo	To mg/mo
			10 mg/m3	10 mg/m3
Copper Phthalocyanine Green	68512-13-0	1 – 10		-
			15 mg/m3	10 mg/m3 NUISANCE DUST

*Chemical(s) that are chronic health hazards. Refer to Section 3 for further information.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. Inhalation: Inhalation of vapor or mist can cause irritation of nose, throat and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to relatively low portion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. If symptoms persist, seek medical attention.

INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

FLASH POINT: No Flash METHOD USED: N/A FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A EXTINGUISHING MEDIA: UPPER: N/A

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication

Date Revised: 11/01/2017

Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep containers from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see Section 10). Keep containers tightly closed. It is advised that material be used within one year of manufacture, rotate stock.

OTHER PRECAUTIONS:

All empty containers under normal use conditions, should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

RESPIRATORY PROTECTION:

No special requirements under normal conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing gloves impervious to solvents and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible. **WORK/HYGIENIC PRACTICES:**

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

PHYSICAL STATE: Liquid	COLOR	
ODOR: Amine or ammoni	SOLUBI	
SPECIFIC GRAVITY (H2O		
BOILING RANGE:	-	EVAPO
COATING V.O.C.: 83 g/l	(0.69 lb/gl)	

OLOR: Various colors OLUBILITY IN WATER: Dilutable VAPOR DENSITY: Heavier than air. VAPORATION RATE: Slower than nBuAc

STABILITY: Stable under normal conditions and handling. CONDITIONS TO AVOID: None known INCOMPATIBILITY (MATERIALS TO AVOID): None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Combustion may liberate toxic byproducts such as carbon dioxide, carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia. HAZARDOUS POLYMERIZATION:

Will not occur.

SENSITIZATION:

None known. CARCINOGENICITY:

The indicated chemical(s) is listed by ICGIH, NTP, or OSHA as a known human carcinogen (See Section 2). IARC has classified respirable crystalline silica in the form of quartz or cristobalite as a group 1 carcinogen. NTP classifies respirable crystalline silica as "reasonably anticipated to be a carcinogen". Because this product is a free flowing liquid, dust inhalation is not an expected route of exposure.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

Date Revised: 11/01/2017

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ENVIRONMENTAL DATA:

No known effects or critical hazards. No data available.

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations maybe more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SHIPPING NAME:

Not regulated.

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE SPECIFIC REQUIREMENTS:

This product does contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

This product contains Crystalline Silica, which when in the respirable form is a chemical know to the state of California to cause cancer, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS CAS NUMBER STATE CODE .

REVISION DATE: 02/20/16								
HMIS CODES:	н	F	R	Р				
	2	0	0	Е				