Date Revised: 11/01/2017

Titanium Dioxide

======================================								
MANUFACTURER ADDRESS :	: DiamaPro System, Inc. 325 West Front Street			N PHONE:	1-800-424-93 1-800-622-20	48		
PRODUCT NAME PRODUCT CODE	Erie, PA 16507 DiamaPro Line Striping Sat DPUV Yellow	fety Yello	NAME OF PRI	EPARER:	Safety Direct	or		
======================================								
HAZARD RISK CL SIGNAL WORD: PICTOGRAM: GHS07 – EXCLAN	WARNING							
HAZARD CLASS		HAZAR	D CATEGORY					
ACUTE TOXICITY SKIN CORROSIO SERIOUS EYE DA TOXIC TO SPECIA TOXICITY – SING	CATEGORY 4 INHALATION CATEGORY 2 CATEGORY 2 AND 2A CATEGORY 3							
HAZARD STATEN H303 H315 H319 H332 H335	 5 Causes skin irritation 9 Causes serious eye irritation. 2 Harmful if inhaled 							
PRECAUTIONARY STATEMENTS:PREVENTION:P261Avoid breathing dust/fume/gas/mist/vapor/spray.P264Wash hands and any exposed area thoroughly after handling.P271Wear protective impervious gloves/OSHA approved eye protection/face protection.								
RESPONSE: P301+P312 If swallowed: Call a Poison Center / doctor if you feel unwell. P302+P352 If on skin: Wash with plenty of water. P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rising. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see on this label) P330 Rinse mouth. P332+P313 If skin irritation occurs: Get medical advise/attention. P363 Wash contaminated clothing before reuse.								
STORAGE: P403+P233 P405	Store in well-ventilated place. Keep container tightly closed. Store locked up.							
DISPOSAL: P501	Store separately . Dispose of contents/container in accordance with local/regional/national regulations.							
======================================								
COMPONENT	CAS NU	MBER	WEIGHT PERCENT	OSHA PEL	URE LIMITS ACGIH TLV			

13463-67-7

1-10

10 mg/m3 10 mg/m3

Date Revised: 11/01/2017

PRIMARY ROUTES OF EXPOSURE: Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. CHRONIC HEALTH EFFECTS:

No anticipated chronic effects. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: No known effects on other illnesses.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

FLASH POINT: No flash METHOD USED: N/A FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

Date Revised: 11/01/2017

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible. **WORK/HYGIENIC PRACTICES:**

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up promptly. Follow OSHA and company guidelines.

PHYSICAL STATE:	Liquid	COLOR:	V
ODOR:	Amine or ammonia odor	SOLUBILITY IN WATER:	D
SPECIFIC GRAVITY (H2O	VAPOR DENSITY:	н	
BOILING RANGE:		EVAPORATION RATE:	S
COATING V.O.C.: 86 g/l	(072 lb/gl)		

Various colors Dilutable Heavier than air. Slower than nBuAc

STABILITY:

Stable under normal conditions and handling. CONDITIONS TO AVOID: None known INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard. **REPRODUCTIVE TOXICITY:**

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life.

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SHIPPING NAME:

Not regulated.

Date Revised: 11/01/2017

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS CAS NUMBER STATE CODE .

REVISION DATE: 09/08/14									
HMIS CODES:	н	F	R	Р					
	2	0	0	Е					