Date Revised: 2/20/2016

MANUFACTURER: DiamaPro Systems, Inc. EMERGENCY PHONE: 1-800-424-9300
ADDRESS: 325 West Front Street INFORMATION PHONE: 1-800-622-2048
Erie, PA 16507 NAME OF PREPARER: Safety Director

PRODUCT NAME: DiamaPro Moisture Control

PRODUCT CODE: DPMC

HAZARD RISK CLASSIFICATION SIGNAL WORD: WARNING

PICTOGRAM:

GHS07 - EXCLAMATION MARK

HAZARD CLASS HAZARD CATEGORY

SKIN CORROSION / CATEGORY 2

IRRITATION

SERIOUS EYE DAMAGE / CATEGORY 2 AND 2A

EYE IRRITATION

HAZARD STATEMENTS:

H303 May be harmful if swallowed
H315 Causes skin irritation
H319 Causes serious eye irritation.
H335 May cause respiratory irritation

PRECAUTIONARY STATEMENTS:

PREVENTION:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash hands and any exposed area thoroughly after handling.

P271 Use only outdoors or in well-ventilated area.

P280 Wear protective impervious gloves/ OSHA approved eye protection/face protection.

RESPONSE:

P301+P312 If swallowed: Call a Poison Center / doctor if you feel unwell.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/ emergency responder.

P321 Specific treatment (see on this label)

P330 Rinse mouth.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advise/attention.
P362 Take off contaminated clothing and wash before reuse.

STORAGE:

DISPOSAL:

====== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ========

COMPONENT	CAS NUMBER	WEIGHT PERCENT	EXPOSURE LIMITS OSHA PEL ACGIH TLV OTHER
Water	7732-18-5	Trade Secret	Not Classified
Sodium silicate	1344-09-8	Trade Secret	Not Classified
	1011 00 0	11440 000101	Acute Tox. 4 (Oral), H302
2,2,4-Trimethylpentane-1,3-dio	monoisobutyrate		· ·
	25265-77-4	Trade Secret	Not Classified
Potassium Silicate	1312-76-1	Trade Secret	
			Acute Tox. 4 (Oral), H302

Date Revised: 2/20/2016

Silicic Acid, lithium salt 12627-14-4 Trade Secret

Not Classified

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

No anticipated chronic effects, MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: Immediately call a poison center or doctor/physician.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

Symptoms/injuries after Inhalation: May cause respiratory irritation.

Symptoms/injuries after skin contact: Causes skin irritation.

Symptoms/injuries after eye contact: Causes serious eye irritation.

Symptoms/injuries after ingestion: May be harmful is swallowed.

FLASH POINT: No flash METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

======= SECTION 6 - ACCIDENTAL RELEASE MEASURES =================================

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

Date Revised: 2/20/2016

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

Wear NIOSH approved respirator when handling.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

======== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ===========================

PHYSICAL STATE: Liquid COLOR: Various colors

ODOR: Slight SOLUBILITY IN WATER: Dilutable SPECIFIC GRAVITY (H2O=1): 1.087 VAPOR DENSITY: Heavier than air. BOILING RANGE: EVAPORATION RATE: Slower than nBuAc

COATING V.O.C.: 0 g/l (0.0 lb./gl.)

======== SECTION 10 - STABILITY AND REACTIVITY DATA ============================

STARII ITY

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

======== SECTION 11 - TOXICOLOGICAL INFORMATION ================================

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life.

Date Revised: 2/20/2016
======================================
This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.
======================================
SHIPPING NAME: Not regulated.
======================================
All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory. This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.
STATE SPECIFIC REQUIREMENTS: This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.
STATE LISTED COMPONENTS CAS NUMBER STATE CODE .
=======SECTION 16 - OTHER INFORMATION ========================
Full text of H-phrases: Acute Tox. 4 (Oral) Acute toxicity (oral) Category 4 Eye Irritant. 2A Serious eye damage/eye irritation Category 2A Skin Irritant. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H302 Harmful if swallowed H315 Causes skin irritation H319 Causes serious eye irritation H335 May cause respiratory irritation