



Protection at the Speed of Light

Diamapro-ESD Clean

Item No: DPESDC – 100 – 3

1. Description

Diamapro® Diamapro-ESD Clean is specifically formulated for use on all types of ESD flooring or static control coated floor. Regular cleaners and detergent compounds leave harmful insulative contaminants behind reducing the static control properties of this specialized flooring system.

Diamapro® Diamapro-ESD Clean does not.

Diamapro® DiamaproESD Clean works well in both mop/bucket and auto-scrubber applications. It will remove dirt and soil while maintaining or even increasing the conductivity of a resinuos ESD flooring system. It comes in a concentrated liquid with an easy to dilution ratio of 1-2 part cleaner to 16 parts of water. 8-16 oz. of cleaner to 1 gallon of water.

2. Recommended Uses

- Ideal for all types of resinous static-control system
- Mild anti-stats rejuvenate the ESD floor finish
- Will not deposit insulative residue
- Deep cleaning power
- Works well with a mop and ringer bucket
- Works well in an auto-scruber fitted with a white pad
- Economical: for light cleanings use the dilution rate suited for your cleaning project. 8-16 oz./gallon water
- VOC free and environmentally friendly

3. Technical Data

pH	6.5-7.5
Abrasives	None
Amonia	None
Acid	None

Phosphates	None
Odor	Mild
Color	Light Green
Solubility in Water	100%
Shelf Life	2 years
Biodegradable	Yes
Soil Suspension	Excellent
Mineral Isolation	Good to Excellent
Coverage Rate	1,000 Sq.Ft./diluted gallon @ 8 oz./gallon

4. Limitations

Do not transport during sub-freezing conditions unless in a climatized transport vehicle.

Is not formulated to be used on carpet or carpet tiles.

Always perform a test panel to determine suitability on all other ESD flooring systems other than **Diamapro® Diamapro-ESD System**.

If the dilution ratio is not followed and used at a rate not listed on this Technical Data Bulletin, the performance of the ESD floor system could be altered.

5. Application Procedures and Instructions

The **Diamapro Diamapro-ESD System** must be swept or vacuumed prior to the start of the cleaning process removing loose dirt and soil.

Daily Use: Dilute **Diamapro® Diamapro-ESD Clean** 8-10 ounces to one gallon of warm water. Mop the floor lightly and allow to dry. Do not Rinse.

Deep Cleaning: Dilute **Diamapro® Diamapro-ESD Clean** 12-16 ounces to one gallon of warm water. Mop the floor lightly and allow to dry. Do not Rinse.



Protection at the Speed of Light

Diama-ESD Clean

Item No: DPESDC – 100 – 3

Auto-Scrubber: Induce 8 ounces of **DiamaPro® Diama-ESD Clean** per gallon of water in the auto-scrubber fitted with a white pad.

After the system has been cleaned and allowed to completely dry, the floor may be spray buffed with **DiamaPro® Diama-ESD Shine** or recoated with **DiamaPro® Diama-ESD Finish** to bring back the original appearance.

6. Availability

DiamaPro® DiamaESD Clean is only available through **DiamaPro® Systems** Authorized Distributors and Applicators. Packaged in 1-5-gallon units. Only **DiamaPro® Systems Authorised Distributors and Certified—Applicators** are allowed to sell the **DiamaPro® Diama-ESD Clean**. For a list of Authorized Distributors or Applicators please contact **DiamaPro® Systems**.

7. Conditions of Sale / Limited Warranty

DiamaPro® Systems warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. In as much as the use of **DiamaPro® Systems'** product by others and other factors affecting product performance are beyond **DiamaPro® Systems'** control, **DiamaPro® Systems** does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose.

SHOULD ANY **DiamaPro® Systems'** PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, **DiamaPro® Systems'** WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF DIAMAPRO

SYSTEMS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.

DiamaPro® Systems does not authorize any person to assume any other liability in connection with the sale or use of its products unless specifically authorized by **DiamaPro® Systems** in writing.

8. Technical Services

The **DiamaPro® Systems** office offers assistance with specifications, performance test data and field services.

9. Disclaimer

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers.

The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products.

FOR INDUSTRIAL AND COMMERCIAL USE ONLY